



Diesel Generators



Output Ratings

Generator Set Model	RT-50
Fuel - HSD	Prime
380 - 415V, 50Hz	50 kVA / 40 Kw

Ratings at 0.8 power factor

Definitions

Standby Rating

The Standby Power rating is only applicable for emergency and standby applications where the generator set serves as the back up to the normal utility source. In installations served by unreliable utility sources (where outages last longer or occur more frequently), where operation is likely to exceed 200 hours per year, the prime power rating should be applied. The Standby Power rating is only applicable for emergency and standby applications where the generator set serves as the back up to the normal utility source. (as defined in ISO 8528-3)

Prime Rating

These ratings are applicable for supplying continuous electrical power (at variable load) in lieu of commercially purchased power. There is no limitation to the annual hours of operation and this model can supply 10% overload power for 1 hour in 12 hours.

Standard Reference Conditions

Ratings in accordance with ISO 8528. All engine performance data based on the above mentioned maximum continuous ratings at Standard Reference Conditions 27°C Air Inlet Temp, 100 Mtrs. A.S.L. 30% relative humidity. Fuel Consumption data at full load with diesel fuel having specific gravity of 0.85 & confirming to BS2869: 1998, Class A2

Engine Technical Data

No. of Cylinders/Alignment:	4 in Line
Cycle:	4 Stroke
Bore/Stroke: mm (in)	97.0 (3.8) / 128.0 (5.0)
Induction:	Turbo Charged
Cooling Method:	Coolant
Governing Type:	Mechanical
Frequency Regulation, no Load to full load	A1
Frequency Regulation, Steady State	ISO 8528 G1
Compression Ratio:	17.5:1
Displacement: l (cu.in):	3.8 (231.89)
Engine Power kW (BHP)	75.7
Air Cleaner Type	Dry Type
Engine Electrical System:	
-Voltage/Ground	12/Negative
-Battery Charger Amps	35/40
Piston Speed, m/sec (ft./sec.)	6.4 (20.9)

Ratings and Performance Data

Engine Make & Model	TATA497TC
Alternator Manufacturer	Crompton Greaves/ Meccalte
Generator Control Unit	Procom
Base Frame	Heavy Duty Fabricated Steel
Canopy/ Acoustic Enclosure	TATA
Circuit Breaker Type/Rating	3 Pole MCB
Frequency	50 Hz
Engine RPM	1500

Available Options

TATA offers a range of optional features to tailor our generating sets to meet your power needs. Options include:

- 1- Upgrade to trailer Mounted Dgset for our rental & Emergency Power supply to Customers
- 2- A wide range of Sound Attenuated Containers
- 3- A variety of generating set control and synchronising panels
- 4- Additional alarms and shutdowns
- 5- A selection of exhaust silencer noise levels

For further information on all of the standard and optional features for this product please contact your local Dealer or write to us at marketing@rishabhengineering.com

Dimensions and Weights of Engine

Length (L) mm (in)	Width (W) mm (in)	Height (H) mm (in)	Dry kg	Wet kg
1136 (44.7)	709 (27.9)	1074 (42.2)	390	410

Dry = With Lube Oil

Wet = With Lube Oil and Coolant

Sound Level

Open Type Genset	102 db at 1 Mtr. In open area	Silent Type Genset with Acoustic Enclosure.	<75 db at 1 Mtr. In open area
------------------	-------------------------------	---	-------------------------------

Ratings in accordance with ISO 8528, ISO 3046, IEC 60034, BS5000

and NEMA MG-1/22. Dgset picture may include optional accessories.

Air Systems

Air Filter Type:	Replaceable Element
Radiator-cooled cooling air, m ³ / min	185
Combustion Air kg/hr	239
Heat rejected to ambient air :	
Engine, kW (Btu/mi n.)	3.6 (204.91)
Restriction: kPa (in H2O)	1.5 (6)
Generator, kW (Btu/mi n.)	4.24 (242)
Air density, kg/m ³ (lbm/ft ³)	1.2 (0.075)

Performance

Engine Speed: rpm 1500

Weight (includes lube oil): kg (lb) 410 (903.8)

Alternator Physical Data

Manufactured for TATA by: Crompton Greaves/ Meccalte

Model: G1R200SB / ECP32 4 C

No. of Bearings: Single Sealed

Insulation Class: H

Winding Pitch Code: 2/3 (M)

Wires: 4

Ingress Protection Rating: IP23

Excitation System: SHUNT

AVR Model: NA

Alternator Operating Data

Voltage Rating, V 415

Voltage Regulation (steady state): +/- 1%

Wave Form NEMA = TIF: 50

Wave Form IEC = THF: 2%

Total Harmonic Content LL/LN: <6.0%

Radio Interference: Suppression is in line with European Standard EN61000-6

Radiant Heat: kW (Btu/min) 50 Hz 3.8 (216)

General Information

Documentation

A full set of operation and maintenance manuals and circuit wiring diagrams.

Generating Set Standards

The equipment meets the following standards: BS5000, ISO 8528, ISO 3046, IEC 60034, NEMA MG-1.22. TATA is a fully accredited ISO 9001:2008 company.

Warranty

All equipment carries full manufacturer's warranty. Extended warranty terms available



Cooling System

Ambient temperature, °C (°F) 45 (113)

Engine jacket water capacity, L (gal.) 3 (0.79)

Radiator system capacity, including engine, L (g): 18.5 (4.89)

Engine jacket water flow, Lpm(g) – Standby: 100(26.4)

Heat rejected to cooling water at rated kW, dry exhaust, kW 32.6

Water pump type – Standby: Impeller

Fan diameter, including blades, mm (in.) 515 (20.27)

Max. restriction of cooling air, intake and discharge side of radiator, kPa 0.125

Lubrication System

Oil Filter Type: Spin-On

Total Oil Capacity: Ltrs. 14

Oil Pan: Ltrs. 9

Oil Type: CH4 15W-40

Oil Cooling Method: Coolant

Exhaust System

Max. Allowable Back Pressure: kPa (in Hg) 2 (0.6)

Exhaust Manifold type Dry

Exhaust flow at rated kW, kg/hr 260.4

Exhaust temperature at rated kW, dry exhaust, °C (°F) 700 (1292)

Exhaust outlet size at engine hookup, mm (in.) 75 (2.95)

Fuel System

Fuel supply line, min. ID, mm (in.) 15 (0.59)

Fuel return line, mm. ID, mm (in.) 10 (0.39)

Max. lift engine-driven fuel pump, m (ft.) 1 (3.28)

Fuel prime pum p Manual

Fuel Filter: quantity, type 1, Spin-on

Recommended fuel HSD-ASTM D2

Fuel tank capacity , L 180

Fuel Consumption* @ 0.85 kg/m³ Density

Diesel, Lph (gph) at % load	Prime Rating
100%	12.0
75%	9.6
50%	7.2

*Tolerance +/- 5%

Controller

LCD Display | Run Time Hours, Current, Voltage, Engine RPM, Frequency, Engine Temperature & Oil Pressure, Battery V, Service Due Hours, Language Option Hindi or English.

LCD Fault Displays | High Water Temperature, Low Lube Oil Pressure, Overspeed, Over & Under Voltage, Over & Under Frequency, E-Stop, Low Fuel Level, Over Load, Charging Alternator/ V-Belt Fault, Auxiliary Fault

Standard Features & Accessories

Master Switch : Start/Off-Reset/Auto

Remote two wire Start/Stop facility

Superior Electronics


Language Option: Hindi & English

Dimensions & Weights


Overall Size, L x W x H, mm(in.) 2850(112.2) x 1100(43.3) x 1550(61)

Weight


Total Genset Weight, Dry, kg (lb.) 1500 (3307)




TOP VIEW



REAR VIEW



RHS VIEW



FRONT VIEW

Dgset Mfr By:- Authorized GOEM | TATA Motors



Rishabh Engineering Co.
 217 Richpalpuri, GT Road, Ghaziabad-201001, UP India-201001
 Visit us at www.rishabhengineering.com
www.linkedin.com/company/rishabh-engineering-co
www.facebook.com/RishabhEngineeringCompany
www.twitter.com/CompanyRishabh



Note: In View Of Continuous Product Upgradation & Design Changes, Above Specifications & Dimensions Are Subject To Change Without Prior Notice.